

# Professional AHD/TVI/CVBS Test Monitor

- CH-L50TM-2



## Monitor Connection



## Specifications

Model	CH-L50TM-2
	<b>Specification</b>
System	AHD/TVI/CVBS
LCD panel	5"
Visible area (mm)	108.0x 64.8
Picture format	16:9
Max. resolution	800x480
Pixel dot pitch (mm)	0.045 x 0.135
Colours	262K
Brightness	350 cd/m <sup>2</sup> (LED BL)
Contrast	500:1
Response time(tr/ta)	10/15 ms
View angle (U/D/L/R)	50/70/70/70
Video input/output	AHD/TVI 1x Composite (BNC) switch. CVBS 2x Composite (BNC) Input /Output Impedance 75Ω Auto Termination.
Audio input	1x (RCA)
Speaker	1x built-in speaker (1 watt)
3D Comb Filter	Yes
3D De-Interlace function	Yes
OSD setting	Yes
Charge Adapter	AC 100-240V 50/60Hz, Adapter DC 12V/2A
DC Output	1x Mini DC Jack (12V/500ma-max)
Battery	Li-ion battery 7.4V/2200mAh
Power consumption	Approx. TBD watt
Dimensions (W*H*D) mm	TBD
Weight	TBD
Operating temperature	0° to 40° C

Subject to technical changes without prior notice. Error excepted.